



Imagine a world of music right at your fingertips. The Nêo 280D makes this a reality. Simply launch your favorite music services app on your smart device and pair it to the Nêo 280D using Bluetooth technology. Then sit back and enjoy the music.

The extraordinary digital engine within the Nêo 280D decodes native DSD up to DSD256, as well as PCM up to 32-bit/384kHz, including DXD. The fully balanced analog stage features an exceptional DC servo circuit and proprietary 3rd order filter for lifelike transparency. The result is a level of fidelity that creates an emotional connection to your music.

Adding the optional **MiND (MOON intelligent Network Device)** module provides convenience and a full graphic interface, allowing you to effortlessly access your digital music library with power and flexibility. Which ever way you use the Nêo 280D, we are convinced that it will become the center of your musical pleasure.

Of course, key features you'd expect in a MOON Nêo Series product are present such as **SimLink™**, RS-232 and IR ports for custom-install environments.

Significant Design Features

- ▲ Fully asynchronous DAC supports native DSD64, DSD128 and DSD256 (USB only) and PCM up to 384kHz (32-bit on USB only).
- ▲ 7 digital inputs (AES/EBU x 1, S/PDIF x 2, TosLink x 2, USB x 1 and Bluetooth x 1) for use with virtually any digital source.
- ▲ aptX® support allows for better quality audio over Bluetooth®.
- ▲ Front panel LED indicators for (i) input signal PCM sampling & DSD rates and (ii) active input.
- ▲ Optional 8th digital input through our **MiND** streaming module (via WiFi or Ethernet).
- ▲ The analog stage is a fully balanced differential circuit for increased dynamic range and headroom, higher resolution, as well as improved signal-to-noise ratio.

Specifications

Frequency response (full range)	2Hz - 100kHz +0/-3dB
THD @ 1kHz, 0dBFS (A-weighted)	0.001%
Intermodulation distortion	0.002%
Dynamic Range	120dB
Signal-to-noise Ratio	118dB @ full output
Channel Separation	116dB
Intrinsic Jitter	1 picosecond RMS
Analog Output @ 0dBFS	2.0 Volts
Analog output impedance	100Ω
PCM Bit-depth range	16 - 32 bits
PCM sampling frequency rates	44.1 - 384kHz
DSD sample rates	DSD64, DSD128 & DSD256
Shipping weight	16 lbs. / 7.5 Kgs
Dimensions (width x height x depth)	16.9 x 3.4 x 13.1 in. 42.9 x 8.6 x 33.3 cm

Available Finishes



Rear Panel

