



## The Music Lovers Line

Inherited from the superb A-S2000 amplifier: purity of sound and elegance of design. Created by those obsessed with great sound, for those who love great music.

Presenting the new generation of Yamaha HiFi.





#### Clear sound in the A-S2000 tradition.









#### Main Features



Dual aluminium-extruded heat sinks ensure effective heat dissipation and help achieve crisp, clean sound.

Gold-plated speaker terminals and

provide highest quality connections.

RCA in/out jacks are durable and



Pure Direct uses the shortest signal route for higher sound purity with low noise and transmission losses.



Yamaha's exclusive Continuously Variable Loudness Control for listening at low volumes.



Centre bar reinforces the internal structure to further prevent vibration from affecting the sound quality.



The built-in iPod Dock has an independent power supply for extremely high S/N ratio.

#### Advanced Features

- 120W x 2 (Max for Europe), 85W x 2 (RMS) high power output
- ToP-ART (Total Performance Anti-Resonance Technology)
- Aluminium-extruded front panel
- Subwoofer out
- Speaker A, B or A+B selection
- Rec Out selector
- Power management (Auto power off)
- Slim-design remote control
- Dimensions (W x H x D): 435 x 151 x 387 mm



The A-S500 offered with black and silver finish available in some areas

#### Optional Accessories



A-S500 Extensive Connection Panel



Rear panel is depending on areas. Banana-plug compatible speaker terminals are not available in some areas.



### Simple design, pure performance.









#### Main Features



ToP-ART

High-end design similar to the A-S2000-the look and feel of the control knobs, for example.

Dual aluminium-extruded heat sinks

and help achieve crisp, clean sound.


ensure effective heat dissipation



Centre bar reinforces the internal structure to further prevent vibration from affecting the sound quality.



The built-in iPod Dock has an independent power supply for extremely high S/N ratio.





Subwoofer Out lets you connect a subwoofer for stronger bass and better overall sound quality.

#### Advanced Features

- 95W x 2 (Max for Europe), 60W x 2 (RMS) high power output
- Pure Direct for short and direct signal path
- Continuously Variable Loudness Control
- Aluminium-extruded front panel
- Speaker A, B or A+B selection
- Power management (Auto power off)
- European sound tuning
- Slim-design remote control
- Dimensions (W x H x D): 435 x 151 x 387 mm




The A-S300 offered with black and silver finish available in some

#### **Optional Accessories**



A-S300 Extensive Connection Panel



Rear panel is depending on areas. Banana-plug compatible speaker terminals are not available in some areas

## Main Features



A-S2000

#### The Look and Texture of Quality

Offers the look and feel of the top-class A-S2000, with elegant aluminium front panel and silky touch volume/selector knobs. You can feel Yamaha's commitment to quality when you touch the knobs.




#### **New Speaker Terminals**

These high grade speaker terminals have gold (A-S500) or silver (other models) plating for best connection and outstanding durability. The pitch between jacks is wider for easier insertion.



#### ToP-ART Sound Quality Design

ToP-ART (Total Performance Anti-Resonance Technology) design uses a symmetrical layout for accurate sound field reproduction and the ART Base to eliminate effects from external vibration.



#### Pure Direct

Music signals travel the shortest possible route, bypassing the buffer amp and tone, loudness and balance controls to virtually eliminate any signal degradation for the purest sound quality.




#### **Highest Quality Parts**

The quality of each individual part, as well as how they work together, basically determines the sound quality of any component. Yamaha uses only very high quality parts, carefully selected and tested.



#### Continuously Variable Loudness Control

Our ears lose sensitivity to high and low frequencies at low volume levels. This control lets you turn down the volume while maintaining the optimum frequency response.



#### Special Power Supply for Clear iPod Sound

The iPod dock has an independent power supply to prevent operating or charging current from the iPod from flowing into the amp ground signal. This ensures optimum iPod sound quality.



#### Balanced System for Minimal Noise

An unbalanced interface is subject to commonmode voltage noise, so Yamaha uses a balanced system to receive the iPod signal. This makes a significant contribution to reducing noise in the system for higher sound quality.



#### New Remote Controls

The A-S500 and A-S300 come supplied with a slim remote unit whose button layout is both easy to understand and use.

#### **OPTIONAL ACCESSORIES**

#### YDS-12 Universal Dock for iPod/iPhone

The optional YDS-12 Universal Dock lets you connect your iPod or iPhone to the receiver.



iPhone not included.



#### YID-W10 Wireless Dock System for iPod/iPhone

The optional YID-W10 ensures that you enjoy maximum sound quality and no lip sync (AV matching) problems.



MirWired



## Recommended Combinations





Full Component System with iPod Wireless Dock

A-\$500 Integrated Amplifier + CD-\$700 CD Player + T-\$500 Tuner + YID-W10 Wireless Dock System + NS-F500 Speaker System



Full Compact System with iPod Wireless Dock

A-S300 Integrated Amplifier + CD-S300 CD Player + T-S500 Tuner + YID-W10 Wireless Dock System + NS-B500 Speaker System + NS-SW500 Subwoofer

# Specifications

Integrated Amplifiers		5 V V V V V	U U U U U
[AUDIO SECTION]		A-S500	A-S300
Maximum Power	(4 ohms, 1 kHz, 0.7 % THD, for Europe)	120 W + 120 W	95 W + 95 W
Minimum RMS Output Power	(8 ohms, 20 Hz-20 kHz, 0.019% THD)	85 W + 85 W	60 W + 60 W
Dynamic Power per Channel	(8/6/4/2 ohms)	130/150/185/220 W	100/120/140/150 W
Input Sensitivity/Impedance	Phono (MM)	3 mV/47 k-ohms	3 mV/47 k-ohms
	CD etc	200 mV/47 k-ohms	200 mV/47 k-ohms
Output Level/Impedance	Rec Out	200 mV/1 k-ohms	200 mV/1 k-ohms
Frequency Response	CD etc, Pure Direct On	10 Hz-100 kHz ±1 dB	10 Hz-100 kHz ±1 dB
Total Harmonic Distortion	Phono (MM) (20 Hz-20 kHz) Rec Out (3 V)	0.025%	0.025%
	CD etc (20 Hz—20 kHz) Sp Out	0.015% (42.5 W/8 ohms)	0.015% (30 W/8 ohms)
Signal-to-Noise Ratio	Phone (MM) (Input Shorted, 5 mV)	88 dB	88 dB
(IHF-A Network)	CD etc [Pure Direct On, Input Shorted, 200 mV)]	100 dB	100 dB
Residual Noise (IHF- Network)		30 μV	30 μV
Volume Variable Range		-89.5dB — +16.5dB	-89.5dB — +16.5dB
Continuous Loudness Control Characteristics Attenuation (1 kHz)		-30 dB	-30 dB
Gain Tracking Error (0 — 99 dB)		0.5 dB	0.5 dB
Audio In / Out		6 / 2	6 / 2
Subwoofer Out		Yes	Yes
[GENERAL SECTION]			
Standby Power Consumption		0.5 W	0.5 W
YID-W10 Connected Standby Power Consumption		1.2 W	1.2 W
iPod Connected Standby Power Consumption		35 W	25 W
Power Management (Auto Power Off)		Yes (6 hours)	Yes (6 hours)
Dimensions	(W x H x D)	435 x 151 x 387 mm	435 x 151 x 387 mm
Weight		10.3 kg	9 kg

<sup>• &</sup>quot;Made for iPod," and "Made for iPhone" mean that an electronic accessory has been designed to connect specifically to iPod or iPhone respectively, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards. iPhone, iPod, iPod classic, iPod nano, and iPod touch are trademarks of Apple Inc., registered in the U.S. and other countries. • Product designs and specifications are subject to change without notice.