

## **LEKTOR 6**

The DALI LEKTOR 6 front baffle features the LEKTOR series' signature silky matt dark grey finish with stylish edge-mounted aluminum snap locks to secure the front grilles. All drivers are mounted with concealed screws, lending a timeless, minimalistic appearance.

The 28 mm (1.1") soft dome tweeter incorporates a powerful ferite magnet system. This innovative driver provides enhanced power handling - continuously and instantaneously - as well as lower power compression, for a more open, vibrant high end.

The pair of 6.5" mid/bass units incorporates lightweight coated woodfiber cones, low-loss suspensions and semi-shielded, double-magnet motors for a highly saturated magnet system. The cone drivers utilize inverted dust caps for improved phase response and structural integrity.

Basing the crossover on a minimal number of select high quality components yields a simple, yet effective filter that preserves the purity of the original electrical signal and, therefore, delivers more musical information to your ears.


DALI LEKTOR 6 is the sum of all these parts, a unique combination of enclosure, drivers and crossover to form a seamless musical system.



## **SPECIFICATIONS**

Frequency range (+/- 3dB) [Hz]:	47,0 - 27.000,0
Sensitivity (2,83 V/1 m) [dB]:	90,5
Nominal impedance [ohms]:	6
Maximum SPL [dB]:	110,0
Recommended amplifier power [W]:	30,0 - 150,0
Crossover frequencies:	700 / 2.900
High frequency driver:	Soft textile dome
Low frequency driver:	Wood fibre cone
Enclosure type:	Bass reflex
Bass reflex tuning frequency [Hz]:	47,5
Connection input(s):	Single wire
Recommended placement:	Floor
Loudspeaker type:	Front
Magnetic shielding:	Semi magnetic shielded
Cabinet body dimensions (HxWxD) [mm]:	256
Max loudspeaker dimensions incl. base and grille	929 X 207 X 285
Loudspeaker weight including base and grille [kg]:	14,2

## **AVAILABLE FINISHES**



## **AWARDS**

