ELECTRA 1037 Be

Product specification sheet



Advanced γ Structure
Massive structure of 2" (50mm)
thick MDF.
No diffraction effect nor vibration.

OPC (Optimum Phase Crossover).

Perfect staging.
Focal binding posts offering high torque and excellent contact.

Front laminar port.
No noise, no distortion.
No dynamic compression.
Spikes and plastic feet supplied.







- ◆100% Focal loudspeakers and drive-units made in France
- Standard finishes, on demand or special personalized finishes
- High size/performance ratio for optimum integration
- ◆ Exclusive Focal technologies

Classic	Signature	
Side panel Standard		
Side panel On demand		
Zebrano	Macassar	Slate Grey

Туре	3-way vented floor standing speaker
Drivers	Three 7" (18cm) "W" woofers 6 ^{1/2"} (16.5cm) "W" midrange 1" (25mm) pure Beryllium IAL inverted dome tweeter
Frequency response (+/-3dB)	33Hz - 40kHz
Low frequency point (-6dB)	26Hz
Sensitivity (2.83V/1m)	93dB
Nominal impedance	8Ω
Minimum impedance	3.3Ω
Crossover frequency	230Hz / 2000Hz
Recommended amplifier power	40 - 400W
Dimensions (HxWxD)	49 ^{3/16} x11 ^{15/16} x15 ^{3/4} " (1 250x303x400mm)
Net weight	112.2lbs (51kg)

A 2007 newcomer, the **Electra 1037 Be** adopts DNA from 1027 Be, but replaces the two 6^{1/2}" (16.5cm) woofers in "W" sandwich by three 7" (18cm) woofers. Authority, rapidity, solidity in the bass, high efficiency, spatialization and definition make it a star product, acclaimed by the world press.







Focal® is a trademark of Focal-JMLab® - BP 374 - 108, rue de l'Avenir - 42353 La Talaudière cedex France - Tel. 00 33 4 77 43 57 00 - Fax 00 33 4 77 37 65 87 - www.focal-fr.com - SCAZ071031/1