

ICE

immersive
cinema
experience



ICE 12.2 P

Description

12" subwoofer with 12" front firing passive radiator. Shallow cabinet for behind the screen or acoustic wall installation. Recommended for small to mid-size rooms.

Specifications

Nominal impedance	8 Ohms
Power handling capacity	Continuous 350 W (AES)
Peak	700 W (AES)
Sensitivity	92dB (1m/1W)
SPL	115dB continuous, 121dB peak (1/8 space, 1m)
Frequency response	Maximum output 121 dB @ 50 Hz 28Hz (-3dB)
Drivers	300 mm long-throw driver with 75 mm voice coil and 300 mm passive radiator
Cabinet	86L bass reflex enclosure with front firing radiator Cabinet is made of premium quality Baltic birch plywood internally cross braced. Black structured painting
Dimensions (HxWxD)	1100 x 550 x 230 mm (height with damping feet 1110 mm)
Weight	30,5 kg

Features

- 1/ 2 steel secure rings with 7 mm pin for safe installation process and operation
- 2/ All cabinet parts are bolt tied
- 3/ Professional grade gold plated push terminals in parallel with Neutrik Speakon connectors
- 4/ Back and front terminals. "Cabinet through" cable tunnel for front terminal access
- 5/ Rear cable channel for close to wall placement
- 6/ Just 230 mm in depth cabinet