

ICE immersive cinema experience



ICE 15.2 P

Description

Powerful bass-reflex subwoofer designed for mid to large –size rooms. ICE 15.2 cabinet is just 300 mm in depth for behind the screen installation.

Specifications

Nominal impedance	4 Ohms
Power handling capacity	Continuous 1400 W (AES) Peak 2800 W (AES)
Sensitivity	98dB (1m/1W)
SPL	128dB continuous, 134dB peak (1/8 space, 1 m) maximum output 128 dB @ 40 Hz
Frequency response	28Hz (-3dB)
Drivers	2x 380 mm long-throw drivers with 100 mm voice coils
Cabinet	236L bass reflex enclosure made of premium quality Baltic birch plywood, internally braced. Black structured painting
Dimensions (HxWxD)	1000 x 1000 x 300 mm (height with damping feet 1010 mm)
Weight	76 kg

Features

- 1/ 2 steel secure rings with 7 mm pin for safe installation process and operation
- 2/ All cabinet parts are bolt tied
- 3/ Professional grade gold plated push terminals in parallel with Neutrik Speakon connectors
- 4/ Back and front terminals. "Cabinet through" cable tunnel for front terminal access
- 5/ Rear cable channel for close to wall placement
- 6/ Just 300 mm in depth cabinet