

ICE**immersive
cinema
experience**

ICE 12.1 P

Description

12" passive subwoofer designed for behind the screen or acoustic wall installation. Recommended for small to mid-size rooms. Can be used as an additional subwoofer together with the ICE 15.2P in multiple subwoofer installation.

Specifications

Nominal impedance	8 Ohms
Power handling capacity	
Continuous	350 W (AES)
Peak	700 W (AES)
Sensitivity	92dB (1m/1W)
SPL	115dB continuous, 121dB peak (1/8 space, 1 m), maximum output: 121dB @ 50 Hz
Frequency response	36Hz (- 3dB)
Drivers	300 mm long-throw driver with 76 mm voice coil
Cabinet	68L sealed box made of premium quality Baltic birch plywood internally cross braced. Black structured painting
Dimensions (HxWxD)	800 x 550 x 230 mm (height with damping feet 810 mm)
Weight	24 kg

Features

- 1/ 2 steel secure rings with 7 mm pin for safe installation process and operation
- 2/ All cabinet parts are bolt tied
- 3/ Professional grade gold plated push terminals in parallel with Neutrik Speakon connectors
- 4/ Back and front terminals. "Cabinet through" cable tunnel for front terminal access
- 5/ Rear cable channel for close to wall placement
- 6/ Just 230 mm in depth cabinet