

Home Cinema Projector

Vivitek HK2288

Ultra HD projector for the home cinema enthusiast



Features

- Ultra HD 4K (3,840 x 2,160) resolution for outstanding details and stunning visuals
- DLP® DarkChip3™ and BrilliantColor™ technologies for optimal black levels and vibrant colorful images
- 2,000 ANSI lumens for an amazing brightness
- Extremely high 50,000:1 contrast ratio for spectacular blacks and outstanding white colors
- Advanced video processor for fluid video streaming and 12-bit programmable RGB colour adjustments
- High Dynamic Range (HDR10) for enriched brightness and impeccable vibrancy for precise natural colors
- REC 709 for an incredible cinematic like movie experience Six segment RGBRGB color wheel delivers outstanding reds, greens and blue color reproductions
- Fine tune and optimize an image with advanced calibrations, including gamma and color management settings
- Advanced HDMI 2.0 (x3) connectors for high quality digital video signals and quick data transfer rates
- Audio ready with built-in 10 watt speaker and audio out port
- Long lasting energy efficient lamps that last up to 4,000 hours (Dynamic Eco. Mode)
- Wide 1.5x zoom range and vertical lens shift for greater installation convenience and flexibility
- Full functioning remote control and intuitive 9 key menu pad for easy control
- Dual infrared sensors for handy remote control from either in front or behind the projector
- Anti-theft security features include: Kensington® security slot, security bar, and PIN lock keypad

Specifications

opcomoduona	
Display Type	DLP® 0.66" TRP by Texas Instruments
Brightness	2,000 ANSI Lumens
Native Resolution	UHD (3840 x 2160)
Maximum Resolution	UHD (3840 x 2160)
Contrast Ratio	50,000:1
Lamp Life/Type	2,500/3,500/4,000 Hours (Normal/Eco./Dynamic Eco. Mode), 310W
Throw Ratio	1.39 - 2.09:1
Image Size (Diagonal)	0.6m - 8.25m (26" - 324.9")
Projection Distance	1.2m - 10m (3.9ft - 32.8ft)
Projection Lens	F= 2.42 - 2.97 f=20.70 - 31.05
Zoom Ratio*	1.5x
Aspect Ratio	16:9
Vertical Scan Rate	24 - 30Hz , 47 - 120Hz
Horizontal Frequency	31 - 131kHz
Speaker	10W (Mono)
Lens Shift Range	Vertical: 5% - 10%
Computer Compatibility	VGA, SVGA, XGA, SXGA, SXGA+, UXGA, WUXGA, Mac, UHD 4K
Video Compatibility	EDTV, HDTV, UHD 4K
I/O Connection Ports	HDMI v2.0 (x3), Audio-Out (Mini-Jack), USB Type A Power (5V/1.5A), Mini-USB (Service), RS-232
Projection Method	Table Top, Ceiling Mount (Front or Rear)
Security Solutions	Security Bar
Dimensions (WxDxH)	430 x 360 x 145mm (16.9" x 14.2" x 5.7")
Weight	9kg (19.81lbs)
Available Colors	White, Black
Noise Level	35dB/TBDdB (Normal/Eco. Mode)
Power Supply	AC 100-240V, 50/60Hz
Power Consumption	450W (Normal Mode), 380W (Eco. Mode), <0.5W (Standby Mode)
Standard Accessories	AC Power Cord, HDMI Cable, Remote Control, Documentation Kit
Optional Accessories	N/A
@2047.V. '. I. V. '. I. '	1 1 (5): 51 : 1 0:1 : 1 1

©2017 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.









Photos







